



NOTES:

1. DETECTOR SHOULD BE MOUNTED AS FOLLOWS:

- A. THE DETECTOR SCINTILLATOR SHOULD BE SET AT THE DETECTOR GAP RECOMMENDED ON THE SIZE SHEET. IF A SIZE SHEET IS NOT AVAILABLE, VEGA RECOMMENDS 50mm [2"] FOR VESSELS WITH MAXIMUM SURFACE TEMPERATURE LESS THAN 60°C AND AT LEAST 150mm [6"] FOR VESSELS WITH MAXIMUM SURFACE TEMPERATURE GREATER THAN 60°C. THIS SPACING IS FROM THE VESSEL'S EXTREME OUTER SURFACE (INSULATION, SHEATHING, ETC.) TO THE SCINTILLATOR SURFACE.
 - B. DO NOT REMOVE ANY INSULATION FROM THE VESSEL DURING INSTALLATION.
 - C. DO NOT PLACE ANY MATERIAL BETWEEN THE VESSEL'S EXTREME OUTER SURFACE AND THE SCINTILLATOR UNLESS DIRECTED BY VEGA.
 - D. MAKE SURE PROCESS MATERIAL OR OTHER FOREIGN MATTER CANNOT ACCUMULATE BETWEEN VESSEL AND SCINTILLATOR.
2. APPROXIMATE WEIGHTS:

- A. 152 mm [6 in] ACTIVE LENGTH, 4.4 kg [10 lb] ALUMINIUM HOUSING OR 9.4 kg [21 lb] STAINLESS STEEL HOUSING
- B. 304 mm [12 in] ACTIVE LENGTH, 5.4 kg [12 lb] ALUMINIUM HOUSING OR 10.4 kg [23 lb] STAINLESS STEEL HOUSING

Projektionsmethode Projection angle		Achtung: Diese Zeichnung stellt die zum Zeitpunkt der Konfiguration gültige Geräteausführung dar. Sie wurde automatisch erstellt, spätere Konfiguration können hiervon abweichen. Attention: This drawing shows the valid instrument version on the configuration date. It was created automatically, later configurations may vary.	
Maßstab Scale	1:4	eID	MB4470-US-PC-3
Originalformat size of origin	B	Produktschlüssel Model Code	POINTRAC 31
		Datum/Date	2019-09-26
Alle Bemaßungen in mm [inch] / All dimensions are mm [inches]			

VEGA
www.vega.com